



EVC-7214

BOX



		Intel LGA1151	6/8/9	i3/i5/i7/i9 CPU, TDP	65W
		Z390			
	BIOS	AMI UEFI/Legac	BIOS		
		2	DDR4 2133/2400/2666 MH	SO-DIMM	up to 64GB
		Win7/Win10/Linu			
I/O	USB	8	USB3.0, 1	USB2.0 T	pe A(for)
	COM	2	:	RS232/422/485(DB9),	
	LED	1	Power, 1	HDD	
	PCIe/M.2/Mini-PCIe	1	Mini-PCIe	SIM	4G/5G)
	Graphics Processor	Intel CPU	(	CPU	)
	Interface	VGA+HDMI			
	SATA/M.2/mSATA	1	mSATA,		
		1	M.2 2280 NVMe SSD		
	LAN IC	4	i210AT		
	Interface	4	RJ45	POE	15W
	Power Input	12V	24V, DC in		
	Power Interface	2Pin			
	Watchdog Timer	1	to 255 sec./min.	per step	
	Dimensions	78mm(W)×200mm(H)×150mm(D)			
	Mounting	/			
	Operating Temp.	-10	50		
	Storage Temp.	-40	85		
	Humidit	95%	@40°C(non-condensing)		
	Shock	With SSD: 15G, IEC 60068-2-27, half sine, 11ms duration			
	Vibration	With SSD:2Grms, IEC 60068-2-64, random	5	500H	1 hr/a is



			LAN	USB3.0	COM	
EVC-7214	Z390	2	4	8	2	1mSATA, 1M.2



EVC-7214	EVC-7214	1
NA	/	1